

Aksa Power Generation has been producing industrial generator sets with an innovative compact design and excellence in quality for over 30 years. Aksa has been providing reliable power through three main production plants and over 15 branch offices worldwide.

Alternator (130 °C Rise)	Voltage	Ph	Pf	Hz	Stand-by Ratings		Prime Ratings	
					kW/kVA	Amp	kW/kVA	Amp
	480/277V	3	0.8	60	250/312	376	227/284	341
	440/254V	3	0.8	60	250/312	410	227/284	372
Marathon MP-217-4A (432CSL6210)	240/139V	3	0.8	60	250/312	752	227/284	682
	240/120V	3	0.8	60	250/312	752	227/284	682
	208/120V	3	0.8	60	250/312	867	227/284	788
	240/120V	1	1	60	190/190	791	171/171	712



Rating Definition

Stand-by Power (Maximum): Power available at variable load in the event of main power network failure. No over load is permitted.

Prime Power: Power available at variable load in lieu of a main power network. Overload of 10% is permitted for 1 hour in every 12 hours of operation.

The above ratings represent the engine performance capabilities to conditions specified in accordance with ISO 8528/5 & ISO3046.

Derating may be required for conditions outside of the test conditions.

Codes, Standards & Standard Features

EPA Certified Tier3 – FLEX engine powered generator set for Mobile / Prime Applications.

The Generator set is designed and manufactured in a facility certified to **ISO9001:2008** standards.

John Deere heavy duty four cycle industrial diesel engine delivers low emission, reliable power, fuel efficiency and fast response to load changes.

Non-proprietary control system provides total gen-set system integrated control, protections, metering, automatic starting/stopping with options of remote control, remote display or remote annunciation.

Aksa Power Generation provides **single source responsibility** for the generator set & accessories.

The generator set, with its components, are **prototype tested** and **production tested**.

Marathon industrial generators meet the requirements of BS EN 60034 and the relevant sections of other international standards.

Heavy duty base frame with integral pad **vibration isolators** eliminates the need for under unit spring vibration isolators.

POWER YOUR FUTURE

Engine Data

Manufacturer	John Deere
Model	6090HF484
Cylinders	6, In-line
Max. power @ rated rpm; kWm (BHP)	287 (385)
Brake mean effective pressure; kPa	2126
Aspiration & Cooling	Turbocharged
Total displacement; L (in ³)	9 (549)
Bore; in. (mm)	4.7 (118.4)
Stroke; in. (mm)	5.4 (136.0)
Compression ratio	16:1
Governor type	Electronic
Engine crankcase vent system	Open

Engine Electrical System

Charging alternator	24V, Negative Ground
Starter rolling current @32 °F; (amp)	600
Min. voltage at ECU during cranking; (dc)	10
Max. allowable start circuit resistance; (Ohm)	0.002
Starter motor rated voltage; (dc)	24
Battery quantity x rating & CCA	2 x 80Ah, 622

Fuel System

ECU Description	L14 Controller
Fuel injection pump	Denso HP4
Governor Type	Electronic
Total fuel flow; lb/hr	450
Fuel temp rise, inlet to return; °C	38
Max fuel inlet temp; °C	80
Max fuel inlet restriction; in.H ₂ O (kPa)	80 (20)
Max. fuel return pressure; in.H ₂ O (kPa)	80 (20)

Fuel Consumption (gal/hr)

110% Load	18.0
100% Load	17.0
75% Load	14.8
50% Load	10.5

Exhaust System

Exhaust gas flow; (m ³ /min)	54.1
Max. allowable exhaust restriction; (kPa)	7.5
Max. exhaust gas temp; (°C)	625
Max. bending moment on turbo outlet; (lb-ft)	5.2

Cooling System

Radiator ambient temp; °C (°F)	50 (122)
Engine coolant capacity; L	16
Min. coolant fill rate; L/min (gal/min)	12(3.2)
Thermostat operation range; °C	82-94
Max top tank temp; °C	110
Min. limiting ambient temp; °C	47
Cooling fan type	Pusher
Min. pressure cap; (psi)	15
Engine air flow; m ³ /min	23.0
Intake manifold pressure; (psi)	32.2
Engine coolant flow; L/min (gal/min)	280 (74)
Engine heat rejection; BTU/min	5521
Air cleaner efficiency	99.9%

Lubrication System

Oil pressure @rated speed; psi	38
Oil pressure at low idle; psi	28
Max. oil carryover in blow by; lb/hr	0.007
Max. air flow in blow by; gal/min	10.6
Max. crankcase pressure; in. H ₂ O (kPa)	2 (0.5)

Alternator Data

Manufacturer	Marathon
Model	MP-217-4A (432CSL6210)
Design	4 Pole, drip proof rotating field
Exciter type	Brushless, self excited P.M.G. option is available
Stator	2/3 winding pitch
Rotor	Single bearing, flexible disc
Leads	12
Voltage regulator	Solid state, Volts/Hz
Insulation	Class H
Temp. rise @ 40°C ambient	130°C Prime
Alternator Cooling	Direct drive centrifugal blower
Max. over-speed; rev/min	2250
Voltage regulator	SE350

kW Rating at 1800rpm/60Hz

480/277V - 3ph – 0.8pf	275
208/120V - 3ph – 0.8pf	275
240/120V - 1ph – 1pf	180

Base-frame & Enclosure

The complete gen-set is mounted entirely on a heavy duty base frame.

Anti vibration isolators are installed between engine/alternator supports and the base frame.

All enclosure parts are designed with module principles without welding.

Enclosure has four doors on each side for easy serviceability and back door for control system.

Exhaust silencer is protected against environmental influences and is internally mounted within enclosure. Exhaust pipe thermally insulated on engine compartment.

All metal enclosure parts are painted by electrostatic polyester powder paint.

Enclosure has lockable fuel filling cap from outside.

Emergency stop switch externally mounted on enclosure.

Control System

DSE7320 is an advanced control system, suitable for a wide variety of single, diesel or gas, gen-set applications. Monitoring and an extensive number of engine parameters, the module displays warnings, shutdowns and engine status information on the back lit LCD screen, illuminated LEDs, remote PC and via SMS text alerts (with external modem).

- UL recognized, NFPA110 Level 1 compatible
- LCD text display, key menu navigation and front panel editing
- Off/Manual/Auto model switch
- Two wire starting/stopping in Auto mode
- Engine exerciser
- IP65 front panel rating with supplied sealing gasket
- Configurable 9 inputs, 8 outputs with expansion capability
- Real time clock provides accurate event logging
- Fully configurable via DSE Configuration Suite PC software
- Remote SCADA monitoring and BMS integration features
- License free PC software

Protections

- Gen. Voltage - under/over
- Gen. Frequency - under/over
- Engine Speed - under/over
- Engine Oil pressure - low
- Engine Temp. - low/high
- Battery Voltage - low/high
- Weak battery
- Fail to start/stop
- Charge fail
- Over current & load(kW/kVA_r)
- Unbalanced load
- Independent Earth Fault
- Reverse Power
- Fuel level - low/high (optional)
- Loss of speed signal

Instruments

- Gen. Voltage (L-L/L-N)
- Gen Frequency
- Engine Speed
- Oil Pressure
- Water Temperature
- Battery Voltage
- Run time
- Engine maintenance due
- Phase sequence
- Pwr. monitoring (kWh / kVAh / kVA_rh)
- Power (kW/kVA/kVA_r)
- Power factor
- Gen. Current (L1-L2-L3)
- Earth current

Convenience Panel Accessories

- (2) Two 20A, 120V GFCI receptacles and breakers
- (3) Three 50A, 240V twist lock receptacles and breakers
- 5-15A, 125V inlet receptacles for battery charger and water heater
- Two wire remote start station
- Generator set voltage adjust rheostat
- (15) 400A rated, stud type quick connect cam-locks

Voltage Selector Switch

- Three positions at 480/277V, 208/120V - 3ph & 240/120 - 1ph
- Product of Salzer or Kraus7Naimer

Standard Features & Accessories

- Trailer w/spare tire and tool box
- Sound Attenuated Steel Enclosure
- Heavy Duty Steel Base-frame
- Residential Grade Silencer Inside Enclosure
- Flex Fuel Lines
- Oil Drain Valve & Extension
- Convenience Panel
- Voltage Selector Switch – 3 position
- Emergency Stop Switch
- Battery, Battery Rack & Cables
- Battery Charger
- Main Line CB
- Jacket Water Heater
- Operations Manual
- 1 Years / 2000hours Limited Warranty

Dimensions & Weight & Sound Level

Gen-set Without Fuel Tank

Type	Generator Set Only	Generator Set On Trailer
L (in.)	144	245
W (in.)	52	96
H (in.)	78	112
Weight (lb)	7400	11900
Sound Level (dBA@23ft)		78

Trailer


- DOT approved 18,000lbs heavy duty triple axle trailer
- Spring axles w/electric brakes
- Breakaway kit with charger
- 12,000lbs front jack and 7,000lbs rear stabilizer jacks
- 7 pin trailer plug
- Tool box and spare tire
- 410gal Single / Double (optional) integrated fuel tank

Circuit Breaker


- 1000Amp capacity main line circuit breaker
- Shunt trip controller by generator set control

Optional Accessories

- Upsized Alternator
- PMG Excitation
- Alternator Anti-condensation Heater
- 4 Position VSS
- Fuel Level Monitoring on Controller & High Fuel Alarm
- Fuel Line Check Valve
- Oil Temperature Gauge
- Oil Heater
- Battery Charger 10Amp
- Battery Heater Blanket
- Main Line CB (100% rated)
- Remote Monitoring and Control
- Remote Annunciator



AKSA POWER GENERATION USA LLC
 371 Exchange Street, West Monroe, LA 71292
 Tel: 318.855.8377
 Fax: 318.855.8381
 E-mail: sales@aksausa.com
 Aksa Power Generation USA is a member of



*Manufacturer reserves the right to make changes in model, technical specifications, color, equipment and accessories without prior notice.